



Infrared Weatherproof IP Camera GSC3615

The GSC3615 is a weather-proof Infrared (IR) wall-mounted bullet IP camera with a 3.6mm lens - making it ideal for wide-angle monitoring of nearby subjects in environments such as banks, hotels, retail, offices, warehouses, and building entrances. This device supports motion detection and smart infrared technology for white balance and exposure to monitor activity at night in outdoor or dark enclosed spaces. The GSC3615 can be managed with GSURF Pro, Grandstream's free video management software, along with other ONVIF-compliant video management systems. It pairs with Grandstream's video phones and GSC3570 HD intercom and facility control station for active end-point monitoring and facility control. By adding weatherproof capabilities, this is an ideal device for increasing security and facility management in any indoor or outdoor area.



Supports motion
detection



Smart infrared technology
for optimal white balance
and exposure



Built-in PoE to power the
device and provide a
network connection



Supports alert
notifications via
outbound voice or video
call & email screenshot



IP66-level weatherproof
capability



Primary stream
1920x1080 and
Secondary stream
640x480



SIP/VoIP support for
video and audio streaming
to endpoints (external
microphone required)

Network Protocol	SIP RFC3261, TCP/IP/UDP, RTP/RTCP, HTTP/HTTPS, ARP, ICMP, DNS (A record, SRV, NAPTR), DHCP, SSH, TFTP, NTP, STUN, SIMPLE, LLDP-MED, 802.1x, TLS, SRTP
Image Sensor Resolution	1/2.9" CMOS Sensor, 1920(H)*1080(V)
Video Compression	H.264/H.265/JPEG/MJPEG
Supported Maximum Video Resolution and Frame Rate	Primary Stream:1920*1080 Secondary Stream: 640*480
Video Output	Network
Audio	Line-In: 1 x 3.5mm, 1-50mVpp; Line-Out: 1 x 3.5mm, 560Ω, 4.0Vpp
Scanning System	Progressive
Image Configuration	Saturation/Brightness/Contrast/Sharpness, White Balance
Focal Length	Fixed 3.6mm
Infrared LED	2x LED, up to 20M, Auto Control
Ethernet	One RJ-45 (10/100Base-T) Port with PoE
ONVIF	Yes, Profile S
Day/Night	Color/ Black &White (IR-CUT)
Motion Detection	Supported
Language Supported	Multi-Language
Privacy Mask	4 Rectangular Zone
Weatherproof Grade	Metal , IP66-level weatherproof capability
Power	DC12V±10%,1A (Power Adapter NOT Included) PoE: Support IEEE 802.3af
Temperature / Humidity	-20 °C ~ 50 °C, RH95% Max
Weight and Dimensions	171 x 73 x 73mm, 430g
Compliance	FCC, CE, RCM, IC