



Outdoor Long-Range High-Performance 802.11 ac Wi-Fi Access Point

GWN7630LR

This outdoor Wi-Fi access point offers extended coverage range and high performance support for both indoor and outdoor deployments, thanks to its innovative antenna and weatherproof design. The GWN7630LR comes equipped with dual-band 4x4:4 MU-MIMO technology and a sophisticated antenna design for maximum network throughput and extended coverage range of up to 300 meters. It uses a controller-less distributed network management architecture in which the controller is embedded within the product's Web user interface for easy administration of locally deployed Wi-Fi APs. The GWN7630LR is also supported by GWN.Cloud, Grandstream's free cloud-based Wi-Fi AP management platform for virtually unlimited deployments. Powered by market-leading technology for advanced QoS, fast roaming, mesh networks, captive portals, 200+ concurrent clients and dual Gigabit network ports, the GWN7630LR is an ideal Wi-Fi access point for low-latency jitter-sensitive real-time applications (such as voice/video-over-Wi-Fi devices & applications) in medium-to-high user density scenarios.



Gigabit

2.33Gbps wireless throughput and 2x Gigabit wireline ports



4x4 MIMO

Dual-band 4x4:4 MIMO technology



PoE

Self power adaptation upon auto detection of PoE/PoE+



Support 200+ concurrent Wi-Fi client devices



300 meters

Up to 300-meter coverage range



QoS

Advanced QoS to ensure real-time performance of low-latency applications



Anti-hacking secure boot and critical data/control lockdown via digital signatures, unique security certificate/random default password per device



Flexibility of detachable/changeable antenna for different application scenarios



Embedded controller can manage up to 50 local GWN series APs; GWN.Cloud offers unlimited AP management

Wi-Fi Standards	IEEE 802.11a/b/g/n/ac (Wave-2)
Antennas	4 detachable/changeable dual-band omnidirectional antennas 2.4GHz, gain 3.5dBi 5GHz, gain 3.5dBi
Wi-Fi Data Rates	IEEE 802.11ac: 6.5 Mbps to 1733Mbps IEEE 802.11a: 6, 9, 12, 18, 24, 36, 48, 54 Mbps IEEE 802.11n: 6.5Mbps to 600Mbps IEEE 802.11b: 1, 2, 5.5, 11Mbps IEEE 802.11g: 6, 9, 12, 18, 24, 36, 48, 54 Mbps <i>*Actual throughput may vary depending on many factors including environmental conditions, distance between devices, radio interference in the operating environment and mix of devices in the network</i>
Frequency Bands	2.4 GHz Radio: 2412 – 2484 MHz 5GHz Radio: 5150-5250MHz, 5250-5350MHz, 5470-5725MHz, 5725-5850MHz <i>*Not all frequency bands can be used in all regions.</i>
Channel Bandwidth	2.4G: 20 and 40MHz 5G: 20, 40 and 80MHz
System Security	WEP, WPA/WPA2-PSK, WPA/WPA2 Enterprise, anti-hacking secure boot and critical data/control lockdown via digital signatures, unique security certificate and random default password per device
MIMO	4x4:4 2.4G (MIMO), 4x4:4 5G (MU-MIMO)
Coverage Range	Up to 300 meters <i>*Coverage range can vary based on environment</i>
Maximum TX Power	2.4G: 27 dBm 5G: 25 dBm <i>*Maximum power varies by country, frequency band, and MCS rate</i>
Receiver Sensitivity	2.4G 802.11b: -96dBm@1Mbps, -88dBm@11Mbps; 802.11g: -93dBm @6Mbps, -75dBm@54Mbps; 802.11n 20MHz: -73dBm @MCS7; 802.11n 40MHz:-70dBm @MCS7 5G 802.11a: -92dBm @6Mbps, -74dBm @54Mbps; 802.11ac 20MHz: -67dBm@MCS8; 802.11ac: HT40:-63dBm @MCS9; 802.11ac 80MHz: -59dBm @MCS9
SSIDs	16 SSID per radio
Concurrent Clients	200+
Network Interfaces	2× autosensing 10/100/1000 Base-T Ethernet Ports
Auxiliary Ports	1× Reset Pinhole
Mounting	Wall mount or pole mount - kits included
LEDs	1× tri-color LEDs for device tracking and status indication
Network Protocols	IPv4/IPv6, 802.1Q, 802.1p, 802.1x, 802.11e/WMM
QoS	802.11e/WMM, VLAN, TOS
Network Management	Embedded controller can manage up to 50 local GWN APs GWN.Cloud offers a free cloud management platform for almost unlimited GWN APs GWN.Manager (coming soon) offers premise-based software controller for up to 3,000 GWN APs
Power and Green Energy Efficiency	PoE 802.3af/ 802.3at; Max Consumption: 16.5W
Environmental	Operation: -30°C to 60°C Storage: -30°C to 70°C Humidity: 5% to 95% Non-condensing
Physical	Unit Dimension: 533.1 × 115 × 40mm; Unit Weight: 564g Unit + Mounting Kits Dimension : 533.1×115 ×62mm; Unit + Mounting Kits Weight : 706g Entire Package Dimension: 258 × 247× 86mm; Entire Package Weight: 978g
Package Content	GWN7630LR 802.11ac Wireless AP, Mounting Kits, Quick Start Guide
Weatherproof Grade	IP66-level weatherproof capability when installed vertically
Compliance	FCC, CE, RCM, IC